

# Product information

## Hypoid Gear Oil (GL5) SAE 80W

PI 29/17/02/2020



### Description

High-performance high-pressure gear oil made from carefully selected base oils and multifunctional "extreme pressure" additives. For powered transmission and axle drives – especially for high-load hypoid transmissions.

### Properties

- reduces running noise
- does not attack common sealing materials
- excellent resistance to aging
- excellent viscosity/temperature properties
- minimizes wear
- high pressure-absorption capability

### Specifications and approvals:

API GL5 • MIL-L 2105 D • ZF TE-ML 17B

**LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:**

MAN 342 Typ M1 • Volvo 97314

### Technical data

SAE class (gear oils)	80W SAE J306
Density at 15 °C	0,880 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	100 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -26°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	96 DIN ISO 2909
Pour point	-27 °C DIN ISO 3016
Flash point	216 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

### Areas of application

For high-load motor vehicle transmissions, particularly axle drives with hypoid gearing.



### Application

During selection, keep to the viscosity class stipulated by the transmission manufacturer. Miscible with all branded gear oils. Fully effective only when used alone. Only use in manual transmissions for which API GL 5 oils have been stipulated.

### Available pack sizes

500 ml Can plastic	1402 D-GB-I-E-P
1 l Can plastic	1025 D-GB-I-E-P
20 l Canister plastic	1046 D-GB-I-E-P
60 l Drum sheet metal	1036 D-GB
205 l Drum sheet metal	20759 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**