

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

#### Pro-Line JetClean Fuel System Cleaner

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Fuel additive

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH  
Jerg-Wieland-Str. 4  
89081 Ulm-Lehr  
Tel.: (+49) 0731-1420-0  
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Acute Tox.	4	H332-Harmful if inhaled.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.03.2021 / 0029

Replacing version dated / version: 02.12.2020 / 0028

Valid from: 08.03.2021

PDF print date: 10.03.2021

Pro-Line JetClean Fuel System Cleaner



Danger

H225-Highly flammable liquid and vapour. H332-Harmful if inhaled. H373-May cause damage to organs through prolonged or repeated exposure. H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260-Do not breathe vapours or spray. P271-Use only outdoors or in a well-ventilated area. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P312-Call a POISON CENTRE / doctor if you feel unwell. P331-Do NOT induce vomiting.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

2-Butoxyethanol

Propan-2-ol

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane

Xylene

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (&lt; 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (&lt; 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
<b>Registration number (REACH)</b>	01-2119475514-35-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	921-024-6 (REACH-IT List-No.)
<b>CAS</b>	---
<b>content %</b>	40-60
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411
<b>Propan-2-ol</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	603-117-00-0

Page 3 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

<b>EINECS, ELINCS, NLP</b>	200-661-7
<b>CAS</b>	67-63-0
<b>content %</b>	15-30
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

<b>Xylene</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119488216-32-XXXX
<b>Index</b>	601-022-00-9
<b>EINECS, ELINCS, NLP</b>	215-535-7
<b>CAS</b>	1330-20-7
<b>content %</b>	10-30
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373

<b>2-Butoxyethanol</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119475108-36-XXXX
<b>Index</b>	603-014-00-0
<b>EINECS, ELINCS, NLP</b>	203-905-0
<b>CAS</b>	111-76-2
<b>content %</b>	5-15
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315 Acute Tox. 4, H332

<b>Hydrocarbons, C10, aromatics, &gt;1% naphthalene</b>	
<b>Registration number (REACH)</b>	01-2119463588-24-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	919-284-0 (REACH-IT List-No.)
<b>CAS</b>	(64742-94-5)
<b>content %</b>	0,1-<1
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Carc. 2, H351 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
 Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
 Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.  
 Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Page 4 of 21  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.03.2021 / 0029  
Replacing version dated / version: 02.12.2020 / 0028  
Valid from: 08.03.2021  
PDF print date: 10.03.2021  
Pro-Line JetClean Fuel System Cleaner

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

### **Eye contact**

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

### **Ingestion**

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### **4.2 Most important symptoms and effects, both acute and delayed**

Headaches

Dizziness

Effects/damages the central nervous system

Unconsciousness

Product removes fat.

Dermatitis (skin inflammation)

Liver and kidney damage

Blood count modifications

Ingestion:

Oedema of the lungs

Lung damage

Chemical pneumonitis (condition similar to pneumonia)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

### **4.3 Indication of any immediate medical attention and special treatment needed**

Symptomatic treatment.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray / alcohol resistant foam / CO<sub>2</sub> / dry extinguisher.

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Explosive vapour/air or gas/air mixtures.

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Keep unprotected persons away.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

GB

Page 5 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Prevent from entering drainage system.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
 Keep away from sources of ignition - Do not smoke.  
 Take precautions against electrostatic charges.  
 Use explosion-proof equipment.  
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
 Observe directions on label and instructions for use.  
 Use working methods according to operating instructions.  
 Exposed employees should have regular medical check-ups.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
 Store product closed and only in original packing.  
 Not to be stored in gangways or stair wells.  
 Observe special storage conditions.  
 Solvent resistant floor  
 Do not store with oxidizing agents.  
 Store in a well ventilated place.  
 Protect from direct sunlight and warming.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 600 mg/m<sup>3</sup>

Chemical Name	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Content %:40-60
WEL-TWA: 600 mg/m <sup>3</sup>	WEL-STEL: ---	---
Monitoring procedures:	- Compur - KITA-187 S (551 174)	
BMGV: ---	Other information: (OEL acc. to RCP-method, paragraphs 84-87, EH40)	

Chemical Name	Propan-2-ol	Content %:15-30
WEL-TWA: 400 ppm (999 mg/m <sup>3</sup> )	WEL-STEL: 500 ppm (1250 mg/m <sup>3</sup> )	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Alcohol 25/a i-Propanol (81 01 631)</li> <li>- Compur - KITA-122 SA(C) (549 277)</li> <li>- Compur - KITA-150 U (550 382)</li> <li>- DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004)</li> <li>- NIOSH 1400 (ALCOHOLS I) - 1994</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> </ul>	

GB

Page 6 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

- Draeger - Alcohol 100/a (CH 29 701)	
BMGV: ---	Other information: ---

Chemical Name	Xylene	Content %:10-30
WEL-TWA: 220 mg/m <sup>3</sup> (50 ppm) (WEL), 50 ppm (221 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 100 ppm (441 mg/m <sup>3</sup> ) (WEL), 100 ppm (442 mg/m <sup>3</sup> ) (EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Xylene 10/a (67 33 161)</li> <li>- Compur - KITA-143 SA (550 325)</li> <li>- Compur - KITA-143 SB (505 998)</li> <li>- INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004)</li> <li>- NIOSH 1501 (HYDROCARBONS, AROMATIC) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999</li> </ul>	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV)	Other information: Sk (WEL)	

Chemical Name	2-Butoxyethanol	Content %:5-15
WEL-TWA: 25 ppm (123 mg/m <sup>3</sup> ) (WEL), 20 ppm (98 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 50 ppm (246 mg/m <sup>3</sup> ) (WEL, EU)	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-190 U(C) (548 873)</li> <li>- DFG Meth.-Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 32-2 (2004)</li> <li>- NIOSH 1403 (ALCOHOLS IV) - 2003</li> <li>- NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996</li> <li>- OSHA 83 (2-Butoxyethanol (Butyl Cellosolve)) - 1990</li> </ul>	
BMGV: 240 mmol butoxyacetic acid/mol creatinine in urine, post shift (BMGV)	Other information: Sk (WEL)	

Chemical Name	Hydrocarbons, C10, aromatics, >1% naphthalene	Content %:0,1-<1
WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---	---
Monitoring procedures:	<ul style="list-style-type: none"> <li>- Draeger - Hydrocarbons 0,1%/c (81 03 571)</li> <li>- Draeger - Hydrocarbons 2/a (81 03 581)</li> <li>- Compur - KITA-187 S (551 174)</li> </ul>	
BMGV: ---	Other information: ---	

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	608	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	699	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	773	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2035	mg/m <sup>3</sup>	

Xylene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - periodic release		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	

Page 7 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
	Environment - water, sporadic (intermittent) release		PNEC	0,327	mg/l	
Consumer	Human - inhalation	Short term, local effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	174	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	14,8	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	108	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	1,6	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	289	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	77	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	180	mg/kg bw/day	

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	140,9	mg/l	
	Environment - oral (animal feed)		PNEC	160	mg/kg feed	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m <sup>3</sup>	

2-Butoxyethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	8,8	mg/l	
	Environment - marine		PNEC	0,88	mg/l	
	Environment - sediment, freshwater		PNEC	34,6	mg/kg dw	
	Environment - soil		PNEC	2,8	mg/kg dw	
	Environment - sewage treatment plant		PNEC	463	mg/l	

Page 8 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

	Environment - sediment, marine		PNEC	3,46	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	9,1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - oral (animal feed)		PNEC	20	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	147	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	44,5	mg/kg bw/d	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	426	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	13,4	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	123	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	38	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	49	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	3,2	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	89	mg/kg bw/d	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	663	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	246	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	75	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	98	mg/m3	

Hydrocarbons, C10, aromatics, >1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls



Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 08.03.2021 / 0029  
Replacing version dated / version: 02.12.2020 / 0028  
Valid from: 08.03.2021  
PDF print date: 10.03.2021  
Pro-Line JetClean Fuel System Cleaner

## 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
Applies only if maximum permissible exposure values are listed here.  
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
These are specified by e.g. EN 14042.  
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

## 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
Solvent resistant protective gloves (EN 374).  
If applicable  
Protective nitrile gloves (EN 374).  
Minimum layer thickness in mm:  
0,4  
Permeation time (penetration time) in minutes:  
> 480  
Protective Viton® / fluoroelastomer gloves (EN 374).  
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
The recommended maximum wearing time is 50% of breakthrough time.  
Minimum layer thickness in mm:  
0,4  
Permeation time (penetration time) in minutes:  
> 480  
Protective Viton® / fluoroelastomer gloves (EN 374).  
Protective hand cream recommended.

Skin protection - Other:  
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
If OES or MEL is exceeded.  
Gas mask filter A (EN 14387), code colour brown  
At high concentrations:  
Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)  
Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
Not applicable

Additional information on hand protection - No tests have been performed.  
In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

## 8.2.3 Environmental exposure controls

No information available at present.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	<100 °C
Flash point:	-18 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Vapours heavier than air.
Density:	0,786 g/ml (15°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	<7 mm <sup>2</sup> /s (40°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No decomposition if used as intended.

### 10.4 Conditions to avoid

Heating, open flame, ignition sources  
 Electrostatic charge

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

#### Pro-Line JetClean Fuel System Cleaner

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value

Page 11 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	5	mg/l/4h			calculated value, Aerosol, Mist
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>20	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant (Analogous conclusion)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Carcinogenicity:						Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Aspiration hazard:						Yes
Symptoms:						drowsiness, unconsciousness, heart/circulatory disorders, headaches, cramps, drowsiness, mucous membrane irritation, dizziness, nausea and vomiting.
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract).

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes

Page 12 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	5000	ppm	Rat		Vapours

<b>Xylene</b>						
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
Acute toxicity, by oral route:	LD50	3523	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	LD50	12126	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LD50	27,6	mg/l/4h	Rat		Does not conform with EU classification., Vapours
Skin corrosion/irritation:						Irritant
Serious eye damage/irritation:						Irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)

Page 13 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Aspiration hazard:						Yes
Symptoms:						breathing difficulties, headaches, dizziness
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract

<b>2-Butoxyethanol</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	1200	mg/kg			
Acute toxicity, by dermal route:	LD50	2275	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	10-20	mg/l/4h	Rat		Vapours
Skin corrosion/irritation:				Rabbit	Regulation (EC) 440/2008 B.4 (DERMAL IRRITATION/CORROSION)	Skin Irrit. 2, Product removes fat.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:				Rat	OECD 451 (Carcinogenicity Studies)	Negative
Carcinogenicity:	NOAEC	125	ppm	Mouse	OECD 451 (Carcinogenicity Studies)	Negative
Aspiration hazard:						No
Symptoms:						acidosis, ataxia, breathing difficulties, respiratory distress, drowsiness, unconsciousness, annoyance, coughing, headaches, gastrointestinal disturbances, insomnia, mucous membrane irritation, dizziness

Page 14 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	<69	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>150	mg/kg bw/d	Rabbit	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	

**Hydrocarbons, C10, aromatics, >1% naphthalene**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixe Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	LC50	>4688	mg/m3	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Reproductive toxicity (Effects on fertility):				Rat	OECD 415 (One-Generation Reproduction Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 452 (Chronic Toxicity Studies)	Negative, Analogous conclusion
Aspiration hazard:						Yes
Symptoms:						drowsiness, headaches, drowsiness, dizziness

Page 15 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	750	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	495	mg/kg	Rat	OECD 411 (Subchronic Dermal Toxicity - 90-day Study)	Negative, Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	1000	mg/m3	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Negative, Analogous conclusion

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line JetClean Fuel System Cleaner							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.
Other information:							According to the recipe, contains no AOX.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:							Concentration in organisms possible.
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,17	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,32	mg/l	Daphnia magna		
12.1. Toxicity to fish:	NOEC/NOEL	28d	2,045	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	NOELR	28d	2,04	mg/l	Salmo gairdneri		
12.1. Toxicity to fish:	LC50	96h	11,4	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	11,4	mg/l	Salmo gairdneri	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	3	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOELR	48h	2,1	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	30	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	81	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable, Analogous conclusion

Page 16 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

12.3. Bioaccumulative potential:	BCF		242-253				
12.4. Mobility in soil:							Adsorption in ground., Product is slightly volatile.
Other information:	AOX		0	%			

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC10	16h	1050	mg/l	Pseudomonas putida		
12.1. Toxicity to daphnia:	EC50	16d	141	mg/l	Daphnia magna		
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		
12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.4. Mobility in soil:	Koc		1,1				Expert judgement
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD		1171	mg/g			

Xylene							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	IC50	72h	4,36	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	98	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		3,16				
12.3. Bioaccumulative potential:	BCF		25,9				



Page 17 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

12.4. Mobility in soil:	H (Henry)		665	Pa*m3/mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

<b>2-Butoxyethanol</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to fish:	LC50	96h	1474	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	21d	>100	mg/l	Brachydanio rerio	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	1550	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1840	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	286	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	>99	%		OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		3,2				Slight
12.3. Bioaccumulative potential:	Log Pow		0,81			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0000016	atm*m3/mol			
12.4. Mobility in soil:	Koc		67				Expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	16h	>700	mg/l	Pseudomonas putida	DIN 38412 T.8	

<b>Hydrocarbons, C10, aromatics, &gt;1% naphthalene</b>							
<b>Toxicity / effect</b>	<b>Endpoint</b>	<b>Time</b>	<b>Value</b>	<b>Unit</b>	<b>Organism</b>	<b>Test method</b>	<b>Notes</b>
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,48	mg/l	Daphnia magna		Analogous conclusion
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to daphnia:	EL50	48h	3-10	mg/l	Daphnia magna		

Page 18 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

12.1. Toxicity to algae:	EL50	72h	11	mg/l	Pseudokirchneriell a subcapitata		
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	58	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		2,8-6,5				High
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixtures

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Residues may present a risk of explosion.

## SECTION 14: Transport information

### General statements

14.1. UN number: 1993

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Classification code:

F1

LQ:

1 L

14.5. Environmental hazards:

environmentally hazardous

Tunnel restriction code:

D/E

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (NAPHTHA (PETROLEUM), ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

EmS:

F-E, S-E

Marine Pollutant:

Yes

14.5. Environmental hazards:

environmentally hazardous

#### Transport by air (IATA)

14.2. UN proper shipping name:



Page 19 of 21  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 08.03.2021 / 0029  
 Replacing version dated / version: 02.12.2020 / 0028  
 Valid from: 08.03.2021  
 PDF print date: 10.03.2021  
 Pro-Line JetClean Fuel System Cleaner

Flammable liquid, n.o.s. (NAPHTHA (PETROLEUM), ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable



#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P5c		5000	50000
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

97,2 %

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections:

2.3, 3, 5, 11, 12, 15

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Acute Tox. 4, H332	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.
Eye Irrit. 2, H319	Classification according to calculation procedure.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 08.03.2021 / 0029

Replacing version dated / version: 02.12.2020 / 0028

Valid from: 08.03.2021

PDF print date: 10.03.2021

Pro-Line JetClean Fuel System Cleaner

STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

STOT RE — Specific target organ toxicity - repeated exposure

Eye Irrit. — Eye irritation

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Skin Irrit. — Skin irritation

Asp. Tox. — Aspiration hazard

STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - dermal

Acute Tox. — Acute toxicity - oral

Carc. — Carcinogenicity

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
etc.	et cetera
EU	European Union
EVAL	Ethylene-vinyl alcohol copolymer
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC (Code)	International Bulk Chemical (Code)
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union for Pure Applied Chemistry
LC50	Lethal Concentration to 50 % of a test population
LD50	Lethal Dose to 50% of a test population (Median Lethal Dose)
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
OECD	Organisation for Economic Co-operation and Development
org.	organic
PBT	persistent, bioaccumulative and toxic
PE	Polyethylene
PNEC	Predicted No Effect Concentration
ppm	parts per million
PVC	Polyvinylchloride
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No.	9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID	Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC	Substances of Very High Concern
Tel.	Telephone
UN RTDG	United Nations Recommendations ON the Transport of Dangerous Goods
VOC	Volatile organic compounds
vPvB	very persistent and very bioaccumulative
wwt	wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.