Product information

Special Tec V 0W-30

Description

Low-friction engine oil based on synthesis technology - ensures reliable prevention of deposits, has an extremely high shear stability, reduces friction in the engine and provides excellent protection against wear. Optimally suited to state-of-the-art diesel and gasoline engines with and without multi-valve technology, Valvetronic, turbochargers and with and without diesel particle filters (DPF) or intercooling. It is especially suitable for long oil change intervals and high engine loads.

Properties

- high shear stability
- saves fuel and reduces pollutant emissions
- tested for turbochargers and catalytic converters
- optimum stability to aging
- outstanding engine cleanliness
- high lubrication reliability
- instant lubrication after cold start

Specifications and approvals:

ACEA A5 • ACEA B5 • API SL • API CF • ILSAC GF-3 • Volvo VCC 95200377

Technical data

SAE class (engine oils)	0W-30 SAE J300
Density at 15 °C	0,845 g/cm³ DIN 51757
Viscosity at 40 °C	51,5 mm²/s ASTM D 7042-04
Viscosity at 100 °C	9,9 mm²/s ASTM D 7042-04
Viscosity at -40°C (MRV)	< 60000 mPas ASTM D 4684

Viscosity at -35°C (CCS) < 6200 mPas **ASTM D 5293**

Viscosity index

DIN ISO 2909

HTHS at 150°C 2.9 - 3.5 mPas

ASTM D 5481

-48 °C

Pour point

DIN ISO 3016

Evaporation loss (Noack) 12,5 %

CEC-L-40-A-93

226 °C Flash point

DIN ISO 2592

Total base number 11,1 mg KOH/g

DIN ISO 3771



Technical data

Sulfate ash <= 1.6 q/100qDIN 51575

Color number (ASTM) 3,0

DIN ISO 2049

Areas of application

This lubricant was developed primarily for use in various Volvo models. Other manufacturers such as Mitsubishi, Renault, Jaquar, Honda etc. also use lubricants with these specifications in various vehicle types.

PI 37/25/08/2020

Application

The operating regulations of the vehicle and engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic	2852 BOOKLET
5 l Canister plastic	2853 BOOKLET
20 l Canister plastic	2363 D-GB
60 l Drum sheet metal	2364 D-GB
205 l Drum sheet metal	2854 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.