Product information

Special Tec F ECO 5W-20



Description

Low-friction motor oil based on synthetic technology. Specially developed for the requirements of Ford gasoline engines. Reliably prevents the formation of deposits, ensures excellent lubrication reliability and enables high fuel savings. In terms of the wear resistance, the requirements of the older Ford standard WSS-M2C913-C are met and, in certain points, even exceeded.

Properties

- high resistance to aging
- instant lubrication after cold start
- outstanding lubrication reliability
- tested for the use with catalytic converters
- outstanding engine cleanliness
- highest fuel economy
- stable to oxidation

Specifications and approvals:

ACEA C5 • API SN • Ford WSS-M2C 948-B • Jaguar / Land Rover STJLR.03.5004

Technical data

SAE class (engine oils) 5W-20 SAE J 300

Density at 15 °C 0,850 g/cm³ DIN 51757

Viscosity at 40 °C 44,0 mm²/s

ASTM D 7042-04

Viscosity at 100 °C 8,20 mm²/s

ASTM D 7042-04

Viscosity at -35 °C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -30°C (CCS) ≤ 6600 mPas

ASTM D5293

Viscosity index 163

DIN ISO 2909

HTHS at 150°C ≥ 2,6 mPas

ASTM D5481

Pour point -45 °C

DIN ISO 3016

Flash point 220 °C

DIN ISO 2592 Evaporation loss (Noack) 12,2 %

CEC-L-40-A-93

Total base number 8,0 mg KOH/g

DIN ISO 3771

Sulfate ash $\leq 0.8 \text{ g}/100\text{g}$

DIN 51575



Technical data

Color number (ASTM) L 2,5

DIN ISO 2049

Areas of application

For Ford gasoline engines except Ford Ka (08/2008-), Focus ST and Focus RS (2004.75 with 2.5 l Duratec-ST (VI5) engine). A lubricant from this specification is prescribed for EcoBoost engines. This motor oil is fully compatible with older versions. Ford also recommends this specification of oil for gasoline engines in which the standards WSS-M2C913-B, WSS-M2C913-C or WSS-M2C925-B are currently prescribed.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed!

Available pack sizes

1 l Canister plastic 3840

D-GB-I-E-P

1 l Canister plastic 21241

ALGERIEN-GB-ARAB-F

5 l Canister plastic 384°

D-GB-I-E-P

5 l Canister plastic 21231

ALGERIEN-GB-ARAB-F

20 l Canister plastic 3842

D-GB-I-E-P

60 l Drum sheet metal 3843

D-GB

205 l Drum sheet metal 3844

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.