## **Product information**

PI 34/25/08/2020

### High Performance Gear Oil (GL4+) SAE 75W-90



#### **Description**

Our fully synthetic high-performance gear oil SAE 75W-90 is a top grade, high-pressure gear oil for high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL4+ is required. High-quality, synthetic-based oil and modern additive technology ensures a broad application range and optimum transmission lubrication under extreme conditions. The low-viscosity characteristics of this gear oil make it also suitable where shifting difficulties exist (e.g. stiffness or noise generation).



- excellent viscosity/temperature properties
- outstanding seal compatibility
- excellent resistance to aging
- excellent wear resistance
- high pressure-absorption capability
- wide viscosity range
- reduces gearshift resistance
- excellent corrosion protection
- reduces transmission noise

#### Specifications and approvals:

API GL4+ • Ford ESD-M2C 175-A

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

VW 501 50 (G50) • ZF TE-ML 08

#### **Technical data**

SAE class (gear oils) 75W-90 SAE J306 Density at 15 °C 0,855 g/cm<sup>3</sup> DIN 51757 Viscosity at 40 °C 81.5 mm<sup>2</sup>/s ASTM D 7042-04 Viscosity at 100 °C 14,3 mm<sup>2</sup>/s ASTM D 7042-04 Viscosity at -40°C (Brook-<= 150000 mPas ASTM D 2983-09 field)

183 Viscosity index

**DIN ISO 2909** 

-60°C

Pour point **DIN ISO 3016** 

200 °C Flash point **DIN ISO 2592** 

#### **Technical data**

Sulfate ash 0,14 q/100q DIN 51575

L 1,5 Color number (ASTM)

**DIN ISO 2049** 

#### Areas of application

For extreme high-load manual, auxiliary, transaxle and hypoid transmissions, where a lubricant complying with API GL 4+ is required.

#### **Application**

The requirements of the vehicle and transmission manufacturers must be adhered to. Can be mixed with mineral oil residue, which remains in transmission/final drive when changing oil.

#### Available pack sizes

500 ml Can plastic	4433 D-GB-I-E-P
1 l Can plastic	4434 D-GB-I-E-P
1 l Can plastic	1125 D-NL-F-GR-ARAB
1 l Can plastic	20462

D-PL-H-RO-TR

1 l Can plastic

USA AND CANADA (-EN-F-)

1 l Can plastic 21258 ALGERIEN-GB-ARAB-F

1 l Can plastic 21354 D-GB-CN

4435 20 l Canister plastic

D-GB-I-E-P

20 l Canister plastic 20014 USA AND CANADA (-EN-

F-l

4436 60 l Drum sheet metal

D-GB

## **Product information**

PI 34/25/08/2020



# High Performance Gear Oil (GL4+) SAE 75W-90

Our information is based on thorough research and may be considered reliable, although not legally binding.