

Product information

megol Motorenoel HD-C3 Super Turbo SAE 20W-50



Description

A motor oil that meets the requirements of all main national and international diesel and gasoline engine manufacturers. That makes it the ideal engine lubricant not only for gasoline engines with or without a catalytic converter, but also for diesel engines including those with exhaust-gas turbochargers, especially the Euro I to Euro III generations.

The instructions issued by the manufacturers are to be followed!

Specifications and approvals:

ACEA A3 • ACEA B4 • ACEA E7 • API SL • API CH-4

Meguin also recommends this product for vehicles that are subject to the following specifications:

Mack EO-M • MAN M 3275-1 • MB 228.3

Characteristic data

SAE class (engine oils)	20W-50 SAE J300
Density at 15 °C	0,880 g/cm ³ DIN 51757
Viscosity at 40 °C	153 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	18,1 mm ² /s ASTM D 7042-04
Viscosity at -20°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -15°C (CCS)	≤ 9500 mPas ASTM D5293
Viscosity index	132 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	7,2 % CEC-L-40-A-93
Flash point	240 °C DIN ISO 2592
Total base number	10,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color number (ASTM)	L5,5 DIN ISO 2049



Available pack sizes

1 l Canister plastic

Part no. 4627
D-GB-F-HR-RUS-GR

5 l Canister plastic

Part no. 4628
D-GB-F-HR-RUS-GR

20 l Canister plastic

Part no. 4886
D-GB