

## Octane Plus



### Description

Octane Plus is a self-mixing combination of agents formulated according to state-of-the-art additive and fuel technology. Octane Plus is for universal use and increases the research octane number (RON) of the fuel by 2-4 points, depending on the RON. Thanks to the increased performance of the fuel, engine damage caused by knocking combustion is prevented. The increase of the octane number ensures low fuel consumption.

### Properties

- improves performance
- increases the octane number
- prevents engine damage caused by knocking combustion

### Technical data

Color / appearance	braun, klar / brown, clear
Base	Additive, Naphta / additives, naphtha
Density at 15 °C	0,817 g/cm <sup>3</sup>
Flash point	63 °C
Pour point	-45 °C
Viscosity at 40 °C	< 7,0 mm <sup>2</sup> /s
Odor	charakteristisch / characteristic
Form	flüssig / liquid

### Areas of application

For increasing the octane number of gasoline.

### Application

One 150 ml can is sufficient for 50 l gasoline. Increases the RON by up to 4 points. Pour Octane Plus into the fuel tank and then top up with fuel. Mixing takes place automatically. Minimum fuel filling of 7 gal. is requested for optimum product performance.

**Note:** Do not store the product at temperatures > 40 °C for extended periods!

### Available pack sizes

150 ml Can sheet metal	8351	GB-ARAB-F
150 ml Can sheet metal	2812	DK/N-S-FIN
150 ml Can sheet metal	2956	GB-GR-I
150 ml Can sheet metal	8346	D-PL-BG
150 ml Can sheet metal	8355	D-E-P
150 ml Can sheet metal	7144	ALGERIEN-GB-ARAB-F
150 ml Can sheet metal	20879	JP
150 ml Can sheet metal	21505	F-D
150 ml Can sheet metal	21349	D-GB-CN
200 l Drum sheet metal	8858	D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**